

Low Profile Cylinder Kit

- Remove truck wheel with the mini-press.
- Fits between chassis and wheel.



**AN APPLICATION:
PRESS TRUCK WHEEL
FROM NAVE WITH THE
MINI-PRESS.**

**Fits between
chassis and wheel.**

HL-1001-D

MINI-PRESS



MINI-PRESS HL1001 ADAPTERS
Capacity: 10 TON
Minimum Height: 88mm
Stroke: 38mm



3 aluminium adapters:
25mm, 50mm en 75mm.



Metal end-part.
Height 10mm.



10mm + 88mm
(98mm)



10mm + 25mm + 88mm
(123mm)



10mm + 50mm + 88mm
(148mm)



10mm + 75mm + 88mm
(172mm)



10mm + 25mm + 75mm + 88mm
(198mm)



10mm + 50mm + 75mm + 88mm
(223mm)



10mm + 25mm + 50mm + 75mm + 88mm
(248mm)

Model Number	Capacity kN	Cylinder Effective Area (cm ²)	Internal Pressure at Capacity (bar)	C	D	E	G	L	M
				Cylinder Bore Ø (mm)	Outside Ø (mm)	Plunger Ø (mm)	Thread	Thread Depth (mm)	Pitch Ø (mm)
CYLINDER CAPACITY: 10 TON = 106 kN									
HL1001	106	15	587	44	70	38	M4	8	26

Accessories

Fitting



Hose



Gauge



Hand Pump

